



# MANATEE COUNTY FLORIDA

## FLOODWAY CONSTRUCTION CERTIFICATION

### POLICY:

A Floodway Construction Certificate shall be submitted and approved by the FEMA Coordinator prior to issuance of a Building Permit for any structure in the floodway. A Licensed Architect or Professional Engineer (P.E.) shall complete the Floodway Construction Certificate.

### PROCEDURE:

1. The Floodway Construction Certification form shall be attached to the approved Floodplain Management Permit when required.
2. This form shall be completed and submitted with the Building Permit Application.
3. The Permitting Technician shall verify that the form bears the signature and embossed seal of an architect or engineer licensed in Florida.
4. The Permitting Technician shall verify that the submitted documents contain structural details and plans signed and sealed by the same architect or engineer that executed the Floodway Construction Certificate.
5. The Plans Examiner shall verify the correctness and completeness of the structural plans and details to assure compliance with the Floodway Construction Certificate. These details should include: footings, pilings, pile caps, grade beams, concrete slabs, connections between pilings and horizontal beams, connections between floor joist and beams, connections between shear walls or exterior walls, floor or roof systems, connections between trusses or rafters and the supporting wall or member, fastener schedules for floor and roof diagrams and for shear walls, breakaway walls, uplift connections and wind bracing. Designation of the connectors and fasteners shall be specific as to load resistance rating. References such as "per code" are not acceptable.
6. The FEMA Coordinator shall review the Certification form and the structural plans prior to the issuance of a Building Permit.
7. A copy of the Certificate shall be attached to the field set of permit plans.
8. A copy of the Floodway Construction Certificate will be placed on both the FEMA Section working file and the "Red Folder" in the Records Management Section. The accepted reference shall be the Coastal Construction Manual FEMA P-55/June 2011.



# MANATEE COUNTY FLORIDA

## FLOODWAY CONSTRUCTION CERTIFICATE

Building Permit No.: \_\_\_\_\_ Owner: \_\_\_\_\_

Street Address: \_\_\_\_\_

City: \_\_\_\_\_ State: \_\_\_\_\_ Zip: \_\_\_\_\_

\*\*\*\*\*

### Section I – Elevation Information

- 1. Bottom of the Lowest Horizontal Structural Member \_\_\_\_\_ ft.
- 2. Base Flood Elevation \_\_\_\_\_ ft.
- 3. Flood Protection Elevation \_\_\_\_\_ ft.
- 4. Elevation of Highest Adjacent Grade \_\_\_\_\_ ft.
- 5. Elevation of Lowest Adjacent Grade \_\_\_\_\_ ft.
- 6. Elevation of Bottom of Pilings or Foundation \_\_\_\_\_ ft.

\*\*\*\*\*

### Section II – Floodway Certification Statement

I certify that based upon development and/or review of structural design, specifications, and plans for construction including consideration of the hydrostatic, hydrodynamic and impact loading involved, that the design and methods of construction are in accordance with accepted standards of practice for meeting the following provisions:

- 1. The bottom of the lowest horizontal structural member of the lowest floor (excluding the pilings or columns) is elevated to or above the Flood Protection Elevation (F.P.E.)
- 2. The pile or column foundation and structure attached thereto is anchored to resist flotation, collapse and lateral movements due to the effects of wind and water loads acting simultaneously on all building components.

\*\*\*\*\*

### Section III – Breakaway Wall Certification Statement

I certify that based upon development and/or review of structural design, specifications, and plans for construction that the design and methods of construction of the breakaway walls are in accordance with accepted standards of practice for meeting the following provisions.

- 1. Breakaway collapse shall result from a safe design loading 20 pounds per square foot. Said walls are capable of resisting a safe design loading of 10 pounds per square foot.
- 2. The elevated portion of the building and supporting foundation system shall not be subject to collapse, displacement, or other structural damage due to the effects of wind and water loads acting simultaneously on all building components.
- 3. The space below the lowest floor is useable solely for parking of vehicles, building access and storage. The area enclosed by solid breakaway walls with one inch clear space between adjacent solid walls does not exceed 299 square feet gross area. The space below is free of obstructions in accordance with FEMA Technical Bulletin 5-August 2008.

\*\*\*\*\*

### Section IV – Certification

Check one: \_\_\_\_\_ Section II    \_\_\_\_\_ Section III    \_\_\_\_\_ Section II and III

Certifier's Name: \_\_\_\_\_

Title: \_\_\_\_\_ License Number: \_\_\_\_\_

Company Name: \_\_\_\_\_

Street Address: \_\_\_\_\_

City: \_\_\_\_\_ State: \_\_\_\_\_ Zip: \_\_\_\_\_

Signature: \_\_\_\_\_ Telephone: \_\_\_\_\_

*(seal required)*